

QATOL QPLEX WRG GREASE

QATOL QPLEX WRG GREASE is a dark grey tacky lubricant provides excellent protection against corrosion in harsh operating conditions such as humidity, heat and gives optimum lubrication particularly during marine applications. QATOL QPLEX WRG GREASE Provides excellent water resistance and maintains and extends the life and performance of wire rope by providing a non-drying film on the external surface of the wire rope. This film protects wire ropes from corrosion, sealing the outside of the cables from moisture and reducing wear and fretting corrosion from contact with external bodies, while lubricating the inner strands

FEATURES & BENEFITS

- QATOL QPLEX WRG GREASE is sufficiently fluid enough to penetrate through the strands to the core of the rope whilst being sufficiently greasy to resist fling off, thus extend the life of wire rope.
- QATOL QPLEX WRG GREASE exhibits excellent lubrication properties which reduces wear on the wires and strands thereby maximizing the service life of the rope
- QATOL QPLEX WRG GREASE is highly resistant to water wash-off and offers outstanding corrosion protection.
- QATOL QPLEX WRG GREASE is a solvent free grease.

SPECIFICATIONS

QATOL QPLEX WRG GREASE meets and exceeds the following Industry Specifications:

DIN-51825

ASTM-D-4950

TYPICAL PROPERTIES

NLGI Grade	Test Method	Results
Color	visual	Dark Grey
NLGI No.	ASTM D 217(1/10mm)	00
Base Type	n/a	Mineral Blend
Base oil viscosity @ 40oC	D 445	220 cSt
Thickener Type	n/a	Sulfonate complex
Worked Penetration	ASTM D 217(1/10mm)	420
Four Ball EP Weld Point, Kg,min	D2596/IP 239	315
Temperature of Use	n/a	150°C
Shelf Life	Declared	5 Years*
Pumpability(Long Distance)	Declared	Excellent

*Stored at room temperature and unopened container

HAZARDS

This grease used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used grease in to drains or the environment. Dispose to an authorized collection point. For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

PACKING

Available Packages: 180Kg, 20Kg, 15Kg, 5Kg, 2Kg, 1Kg, 0.5Kg