

QATOL QPLEX MP Greases

QATOL QPLEX MP Grease is Lithium based Multipurpose grease capable to survive at High thermal and powered loads.

QATOL QPLEX MP has outstanding resistance to water wash-outs and provides excellent corrosion protection to the machines.

APPLICATION

QATOL QPLEX MP are multipurpose grease pre-eminently suitable for passenger car, light truck and leisure vehicle applications.

QATOL QPLEX MP grease is also designed for the lubrication of Rolling mill bearings.

QATOL QPLEX MP provides the following advantages:

- I. Multipurpose application
- II. Super wear protection
- III. Appropriate for a wide range of temperature.

SPECIFICATIONS

ISO 6743-9: L-XBCEA 2

DIN 51502: K2K -25

&

ISO 6743-9: L-XBCEA 3

DIN 51502: K3K -20

Meets the requirement of Mercedes-Benz, Specifications for Operating Fluids Sheet 267.0

KEY PROPERTIES

QATOL QPLEX MP GREASE	Test Method	NLGI2	NLGI3
Thickener Type	-	Li-Based Soap	Li-Based Soap
Worked Penetration @ 25°C, 60 strokes	ASTM D 217,1/10mm	265 - 295	220 - 250
Drop Point, °C	ASTM D 2265, °C	180 min	180 min

HAZARDS

This grease used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.

For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

OPERATING RANGE

Recommended operating range is -20 °C to 120 °C

PACKING

Available Packages: 180Kg, 15Kg, 1Kg, 0.5 Kg