

## QATOL SUPER PLUS GASOLINE ENGINE OIL SAE 10W30

### SEMI SYNTHETIC - API SL/CF



QATOL Super Plus Gasoline Engine Oil (Semi Synthetic) SAE 10w30 is Ultra High Performance for a variety of vehicles. This Ultra High Performance Engine Oil can be used all over the year. The good cold flow properties of QATOL Super Plus Gasoline Engine Oil (Semi Synthetic) SAE 10w30 are ensuring fastest lubrication at all parts of the engine. Friction and wear will be reduced and by that the fuel efficiency improved. QATOL Super Plus Gasoline Engine Oil (Semi Synthetic) SAE 10w30 guarantees engine durability under city conditions as well as under top speed highway running conditions.

#### APPLICATIONS:

- For all types of modern gasoline-powered engines found in passenger cars, SUVs, light vans and light trucks.
- shall be used for passenger cars and light duty vehicles with gasoline engines, As all season's motor oil.
- QATOL Super Plus Gasoline Engine Oil (Semi Synthetic) SAE 10w30 offers good cold start and fuel economy in the winter as well as high thermal stability in summer.
- All types of gasoline Sports cars with large displacements and high outputs, high-performance passenger cars, racing- specification cars, etc.
- Suitable & exceeds the performance level of most European, Japanese and American car manufactures.

#### FEATURES AND BENEFITS:

- Formulated for reliable protection against harmful sludge and varnish formation and helps improve engine performance.
- Outstanding oxidation Stability at high temperatures.
- Excellent Engine cleanliness and water resistance.
- Superior engine protection & eliminates seasonal Oil change.
- Ensuring sustainable high performance and extended oil drain intervals.
- Sustainable wear protection for all engines

#### SPECIFICATIONS:

API SL/CF

## KEY PROPERTIES:

PROPERTIES	TEST METHOD	TYPICAL VALUES	UNIT
Density @ 35 °C	ASTM D 4052	0.85	g/ml
Kinematic Viscosity @ 40 °C	ASTM D 445	69	mm <sup>2</sup> /s
Kinematic Viscosity @ 100 °C	ASTM D 445	11	mm <sup>2</sup> /s
Viscosity Index	ASTM D 2270	140 typ	-
Flash Point, CoC	ASTM D 92	228	°C
Pour Point	ASTM D 97	-39	°C

## HAZARDS

This oil used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

## PACKING

Available Packages: 1000L, 208L, 60L, 20L, 5L, 4L, 1L