

QATOL SUPER POWER DIESEL ENGINE OIL SAE 15W40 (API-CF4/SL)

High-quality heavy-duty Multi grade Diesel Engine Oil.



PRODUCT DESCRIPTION:

QATOL DIESEL ENGINE OIL SAE 15W40 is a high-quality heavy-duty engine oil. This product can be used in 4-stroke gasoline and diesel engines. This product can be used all year round and is intended for passenger cars, light vans and trucks. This product is particularly suitable for large mixed fleets and can be used in diesel engines that are naturally aspirated and/ or equipped with turbochargers. This formulation includes high detergent and dispersant additives and is specifically developed to function well in extreme working conditions.

APPLICATIONS:

QATOL DIESEL ENGINE OIL SAE 15W40 recommended for both diesel and gasoline engines, which are naturally aspirated, turbo-charged or super charged.

QATOL DIESEL ENGINE OIL SAE 15W40 recommended for use in European, Japanese, and US turbocharged and non-turbocharged diesel engines. Also it is most suitable for automotive petrol engines and 4 wheel drives due to the high level of detergents/dispersants that provide excellent protection from typical city stop/start operation that promotes acid sludge formation.

BENEFITS:

- Excellent oxidation and thermal stability under severe operation.
- Super detergent-dispersant characteristics.
- Prevents harmful foaming.
- Excellent anti-corrosion and anti-rust properties.
- Prolongs engine life and improves running efficiency
- Excellent TBN retention effectively neutralizing the acidic by-products of combustion

SPECIFICATIONS:

API CF-4/SL

KEY PROPERTIES:

PROPERTIES	TEST METHOD	TYPICAL VALUES	UNIT
Density @ 35 °C	ASTM D 4052	0.87	g/ml
Kinematic Viscosity @ 40 °C	ASTM D 445	110	mm ² /s
Kinematic Viscosity @ 100 °C	ASTM D 445	13.9	mm ² /s
Viscosity Index	ASTM D 2270	126	-
TBN	ASTM D 2896	11.9	mg KOH/g
Flash Point, CoC	ASTM D 92	236	°C
Pour Point	ASTM D 97	-30	°C
Dynamic Viscosity @ - 20 °C	ASTM D 5293	<7000	cP

AVAILABLE PACKAGES: 208L, 25L, 20L, 5L, 4L, 1L.