

QATOL ULTRA PLUS LD SAE 5W40

API CK4/SN, SCANIA LDF-4, MB 228.51/228.52

QATOL ULTRA PLUS LD SAE 5W40 is developed according to the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain all required benefits for your engine.

QATOL ULTRA PLUS LD SAE 5W40 has been developed to meet the most stringent requirements of latest generation heavy duty diesel engines and gasoline engines of wide range of carmakers.

QATOL ULTRA PLUS LD SAE 5W40 is an all-season synthetic oil that can be used under the most difficult operating conditions (highways, congested city traffic, etc.).

APPLICATIONS

QATOL ULTRA PLUS LD SAE 5W40 is suitable & exceeds the performance level of most European, Japanese and American heavy-duty engines manufactures requiring API CK4/SN oils.

SPECIFICATIONS

QATOL ULTRA PLUS LD SAE 5W40 meets and exceeds requirements of international standards and manufacturer requirements

API CK4/SN, ACEA E6-16/E9-16/E7-22/E8-22/E11-22, JASO DH-2, DAIMLER TRUCKS DTFR 15C100/110/120 (ex MB 228.51/228.52), MAN 3775, VOLVO VDS -4.5, RENAULT TRUCKS RLD-3, MTU Type 3.1, DEUTZ DQC IV-18LA, CUMMINS CES 20086, Mack EOS-4.5, DDC 93K222, SCANIA LDF -4 LA Level, CATERPILLAR ECF-3, FORD WSS-M2C213-A1 (IP), DAF PSQL 2.1E-LD

FEATURES & BENEFITS

- Excellent overall performance and engine protection.
- Excellent low temperature start-up engine protection.
- Excellent frictional properties that aid fuel economy.
- Excellent cleaning and wear protection.
- For all types of modern heavy duty diesel engines.
- It is perfectly adapted to all vehicles equipped with the exhaust after treatment devices.

TYPICAL PROPERTIES

QATOL ULTRA PLUS LD SAE 5W40 API SN		Typical value
Density @ 35°C	kg/m ³	0.835
Kinematic Viscosity:		
mm ² /s @ 40 °C		91
mm ² /s @ 100 °C		14.6
Viscosity Index		160 Typical
Flash Point COC, °C		228
Pour Point, °C		-39

HAZARDS

This oil used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

PACKING

Available Packages: 1000L, 208L, 60L, 20L, 5L, 4L, 1L