

## QATOL CPT-NGEO SAE 40

### Gas engine oil with extended drain performance

#### PRODUCT DESCRIPTION:

Premium CNG/LNG oil formulated to deliver outstanding protection and long drain performance in a wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engine applications.

QATOL CPT-NGEO SAE 40 is specifically formulated to work with compressed natural gas (CNG) , and liquefied natural gas (LNG)-fueled main and auxiliary engines on a range of vessels.

#### APPLICATIONS:

Wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engines

#### FEATURES AND BENEFITS:

- Great performance for medium and heavy-duty vehicles using CNG, LNG or LPG.
- Excellent engine cleanliness
- Sludge control , and valve, or piston deposits in field trials and engine tests.
- Oil oxidation/nitration control

#### SPECIFICATIONS:

MWM-Natural Gas.

MWM-Biogas.

Rolls-Royce B35:40.

Rolls-Royce C26:33.

Rolls-Royce K-G1/G2/G3/G4 .

WärtsiläSG34, SG50.

Cummins QSK 60.

#### KEY PROPERTIES:

PROPERTIES	TEST METHOD	TYPICAL VALUES	UNIT
Density @ 15 °C	ASTM D 4052	0.87	g/ml
Kinematic Viscosity @ 40 °C	ASTM D 445	131.3	mm <sup>2</sup> /s
Kinematic Viscosity @ 100 °C	ASTM D 445	15.3	mm <sup>2</sup> /s
Viscosity Index	ASTM D 2270	117	-
Flash Point, CoC	ASTM D 92	228	°C
Pour Point	ASTM D 97	-27	°C

AVAILABLE PACKAGES: 208L , 25L, 20L, 5L, 4L, 1L.