

QATOL CNG ENGINE OIL CPT SAE 15W40

High-Performance Heavy-Duty Engine Oil for CNG and LNG Fueled Trucks and Buses

QATOL CNG ENGINE OIL CPT SAE 15W40 is a high-performance heavy-duty engine oil formulated specifically for spark ignited CNG and LNG fueled truck and bus engines. It provides excellent performance in the challenging operating environments presented by CNG (Compressed Natural Gas) and LNG (Liquefied Natural Gas) and offers extended drain interval capability. The optimized Ash Content in the oil helps in protecting against excessive valve recession & spark plug fouling.

APPLICATIONS

QATOL CNG ENGINE OIL CPT SAE 15W40 is recommended for Light & Heavy vehicles running on CNG & LNG.

FEATURES & BENEFITS

- Extended Drain Interval
- Good control on Oxidation & Nitration
- Exceptional control on Deposits & Wear
- Ensures engine durability
- Reduced NOx formation

SPECIFICATIONS

API CI-4
CUMMINS CES- 20074

TYPICAL PROPERTIES

QATOL CNG ENGINE OIL CPT SAE 15W40		15W40
Density kg/m ³		0.9651
Kinematic Viscosity:		
mm ² /s @ 40 °C		110.7
mm ² /s @100 °C		15.0
Viscosity Index		145
Flash Point COC, °C		224
Pour Point, °C		-36

HAZARDS

This oil used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.

For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

PACKING

Available Packages: 1000L,208L,60L,20L, 5L, 4L,1L