

QATOL SPT-NGEO SAE 15W40

Gas engine oil with Steel Piston Technology

PRODUCT DESCRIPTION:

Premium CNG/LNG oil formulated to deliver outstanding protection and long drain performance in a wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engine applications with Steel Piston Technology.

QATOL SPT-NGEO SAE 15W40 is specifically formulated to work with compressed natural gas (CNG) , and liquefied natural gas (LNG)-fueled main and auxiliary engines on a range of vessels.

APPLICATIONS:

Wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engines with Steel Piston Technology.

FEATURES AND BENEFITS:

- Great performance for medium and heavy-duty vehicles using CNG, LNG or LPG.
- Excellent engine cleanliness
- Sludge control , and valve, or piston deposits in field trials and engine tests.
- Oil oxidation/nitration control

SPECIFICATIONS:

INNIO JENBACHER : TYPE 2 / TYPE 3 / TYPE 4 (B&C) / TYPE 6 (E &F).

KEY PROPERTIES:

PROPERTIES	TEST METHOD	TYPICAL VALUES	UNIT
Density @ 35 °C	ASTM D 4052	0.88	g/ml
Kinematic Viscosity @ 40 °C	ASTM D 445	115	mm ² /s
Kinematic Viscosity @ 100 °C	ASTM D 445	14.5	mm ² /s
Viscosity Index	ASTM D 2270	128	-
Flash Point, CoC	ASTM D 92	228	°C
Pour Point	ASTM D 97	-27	°C
Dynamic Viscosity @ -20 °C	ASTM D 5293	<7000	cP

AVAILABLE PACKAGES: 208L , 25L, 20L, 5L, 4L, 1L.