

QATOL SUPER POWER DIESEL ENGINE OIL SAE 10W

API CF-4, CAT TO2



QATOL SUPER POWER DIESEL ENGINE OIL SAE 10W CF4, TO2 engine oil used in hydraulic applications where mobile equipment manufacturers recommend SAE 10W engine oil. It has been developed to provide special anti-wear protection to minimize mobile equipment pump wear also includes rust and corrosion inhibitors to protect the hydraulic system working surfaces

APPLICATIONS

QATOL SUPER POWER DIESEL ENGINE OIL SAE 10W CF4, TO2 is recommended for use in both diesel and petrol engines with or without turbocharger, such as:

- Commercial diesel vehicle engines
- Stationary diesel engines
- Construction machines and agricultural units

In addition, the product can be used in hydraulic systems, hydraulic clutches, gearboxes, torque converters and retarders for which the manufacturer prescribes the use of a high-performance single-grade engine oil.

SPECIFICATIONS

QATOL SUPER POWER DIESEL ENGINE OIL SAE 10W meets and exceeds the following OEM and International specifications:

- API CF-4
- Caterpillar TO-2

FEATURES & BENEFITS

- High-performance single-grade engine oil
- High viscosity index
- High dirt dispensing capacity

- Stable lubricant film
- Excellent cleaning capacity
- High thermal stability
- Excellent wear and corrosion protection

TYPICAL PROPERTIES

QATOL SUPER POWER DIESEL ENGINE OIL SAE 10W CF-4	TYPICAL RESULTS
Density kg/m ³	0.8566
Kinematic Viscosity:	
mm ² /s @ 40 °C	38.36
mm ² /s @ 100 °C	6.48
Viscosity Index	121
TBN mg KOH/g	7.4
Flash Point COC, °C	224
Pour Point, °C	-39

HAZARDS

This oil used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

PACKING

Available Packages: 1000L, 208L, 60L, 20L, 5L, 4L, 1L