

QATOL SUPER POWER DIESEL ENGINE OIL SAE 30 (TO-2) (API CF-4)



High performance mono grade diesel engine oils are specially designed to lubricate a wide range of diesel engine oils.

PRODUCT DESCRIPTION:

QATOL SUPER POWER DIESEL ENGINE OIL SAE 30 (TO-2) Diesel SAE 30 Motor Oil provides premium quality service in both diesel and gasoline engines, and are specially formulated for heavy-duty diesel engines operating both on-and off highways. The anti-wear agents used in this product range provide excellent protection against metal to metal contact, minimizing engine wear and effectively extending engine life. The high thermal stability provides outstanding high temperature protection.

QATOL SUPER POWER DIESEL ENGINE OIL SAE 30 (TO-2) SAE 30 Motor Oil contains the latest development in dispersant technology to resist oil thickening caused by this soot. The dispersant minimizes sludge formation and effectively keeps particles in suspension to extend filter life.

APPLICATIONS:

QATOL SUPER POWER DIESEL ENGINE OIL SAE 30 (TO-2) Diesel SAE 30 Motor Oil is recommended for both on and off-road heavy duty applications that require up to API CF-4 Service level, especially older engines.

QATOL SUPER POWER DIESEL ENGINE OIL SAE 30 (TO-2) SAE 30 Motor Oil is also suitable for use in hydraulic systems of heavy construction equipment. Always refer to the vehicle's owner manual for the correct viscosity choice.

BENEFITS:

Helps extend engine life

- Single line of motor oil for mixed fleets
- Minimizes piston and combustion chamber deposit
- Fights sludge and varnish
- Effectively neutralizes acids to help keep corrosive wear to a minimum
- Contains anti-wear and anti-scuff agents

SPECIFICATIONS:

API CF-4

Caterpillar TO-2

KEY PROPERTIES:

PROPERTIES	TEST METHOD	TYPICAL VALUES	UNIT
Density @ 35 °C	ASTM D 4052	0.883	g/ml
Kinematic Viscosity @ 40 °C	ASTM D 445	100.2	mm ² /s
Kinematic Viscosity @ 100 °C	ASTM D 445	11.13	mm ² /s
Viscosity Index	ASTM D 2270	95	-
TBN	ASTM D 2896	7.0	mg KOH/g
Flash Point, CoC	ASTM D 92	230	°C
Pour Point	ASTM D 97	-24	°C

AVAILABLE PACKAGES: 208L , 25L, 20L, 5L, 4L, 1L.