

QATOL SUPER GT GASOLINE ENGINE OIL SAE 20W50 (API-SF/CF)

High Performance motor oil for passenger cars.



PRODUCT DESCRIPTION:

QATOL GASOLINE ENGINE OIL SAE 20W50 Multi grade engine oil for the lubrication of gasoline and diesel engines of passenger cars with natural aspiration or turbo charging. This oil is characterized by a combination of good detergent and good dispersion properties.

APPLICATIONS:

Modern automotive engines are subjecting the motor oil to increasingly severe conditions. Increased power output, extended drain intervals, more stop-go operation and high operating temperatures are additional factors influencing the need for higher motor oil quality. QATOL GASOLINE ENGINE OIL SAE 20W50 oils have been specially developed to cope with these arduous conditions using stringent performance tests.

QATOL GASOLINE ENGINE OIL SAE 20W50 is recommended for four-stroke gasoline engines, used in cars, light trucks, motorcycles, some types of boats and other mobile and stationary equipment when a lubricant that meets API SF classification is required by the manufacturer.

QATOL GASOLINE ENGINE OIL SAE 20W50 can also be used in vehicles fueled by compressed natural gas (CNG) and liquefied petroleum gas (LPG) when a product of API SF classification is required.

FEATURES AND BENEFITS:

- Superior engine protection during start up
- Superior engine wear protection
- Minimizes sludge formation
- Reduces wear by controlling soot deposits
- Extension of engine's lifetime
- Reduced high temperature engine deposits
- Reduces wear due to advanced base oils
- Can be used in both Diesel & LPG engines
- Provides improved fuel economy
- Suitable for hydraulically actuated injectors
- Safe for wet clutch motorcycles
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures

SPECIFICATIONS:

API SF/CF

KEY PROPERTIES:

Properties	TEST METHOD	Typical Values	UNIT
Density @ 35 °C	ASTM D 4052	0.88	g/ml
Kinematic Viscosity @ 40 °C	ASTM D 445	166	mm ² /s
Kinematic Viscosity @ 100 °C	ASTM D 445	19	mm ² /s
Viscosity Index	ASTM D 2270	127	-
TBN	ASTM D 2896	6	mg KOH/g
Flash Point, CoC	ASTM D 92	240	°C
Pour Point	ASTM D 97	-27	°C
Dynamic Viscosity @ -15 °C	ASTM D 5293	<9000	cP

AVAILABLE PACKAGES: 208L, 25L, 20L, 5L, 4L, 1L.