

QATOL ULTRA TRANS ATF DEX VI

Fully Synthetic

QATOL ULTRA TRANS ATF DEX-VI is a fully synthetic high-performance fluid meeting the most demanding requirements of GENERAL MOTORS 6-speed automatic transmission system. Exceeds the service fill of 2006 and new GM vehicles, where a DEXRON-VI fluid is recommended.

QATOL ULTRA TRANS ATF DEX-VI provides effective wear protection and optimal friction characteristics for smooth gear shifts. Highly stable to mechanical wear at various working temperature, consistent fluid characteristics and excellent shear stability to provide robust protection of transmission systems. Engineered for longer drain intervals versus the older DEXRON fluids.

APPLICATIONS

Recommended for use in modern automatic transmissions and steering gears of passenger cars, vans and light commercial trucks where DEXRON-VI fluid is required. Backward compatible to older GM vehicles whenever DEXRON is specified.

SPECIFICATIONS

- GM DEXRON®-VI
- FORD MERCON®
- CHRYSLER ATF+4
- FORD WSS M2C 922A1
- FORD FF-WSS-M2C-938A
- VW/Audi G052 162, G052 990, G055 025

QATOL ULTRA TRANS ATF DEX-VI is suitable for use in various American, Asian, European OEMs. For GM, HONDA, HYUNDAI, CHRYSLER, FORD, KIA, ISUZU, MERCEDES BENZ, MITSUBISHI, NISSAN, TOYOTA, OPEL and other makers requiring a DEXRON-VI automatic transmission fluid.

FEATURES & BENEFITS

- Superior wear protection and reliable friction properties for a consistent operation of transmission systems, contributing to prolonged transmission life.
- Reduced friction to improve automatic gearboxes reaction during engine start up.

- Excellent oxidation properties to prevent fluid breakdown at high operating temperatures, making fluid stable under severe driving conditions. Extended drains of up to 400,000 km.

TYPICAL PROPERTIES

QATOL ULTRA TRANS ATF DEX VI		TYPICAL VALUES
Color		Red
Density @ 35°C , kg/m3		0.83
Kinematic Viscosity mm ² /s @100 0C		5.5
Kinematic Viscosity mm ² /s @40 0C		26.76
Viscosity Index		155

HAZARDS

This oil used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

PACKING

Available Packages: 1000L,208L,60L,20L, 5L, 4L,1L