



QATOL ULTRA TRANS ATF SP-IV

Fully Synthetic

QATOL ULTRA TRANS ATF SP-IV is a fully synthetic low viscosity automatic transmission fluid designed for 6 speed electronically controlled system of passenger cars which require a fluid with SP-IV specification. Delivers fuel efficiency versus the conventional ATFs.

Qatol Ultra Trans ATF SP-IV provides improved performance without the need of any supplemental additives. Its superior frictional characteristic ensures smooth gear shifts and gives optimum protection against wear. Delivers the highest performance even in high operating temperature conditions.

APPLICATIONS

Recommended for use in 6 speed automatic transmissions where SP-IV fluid is required. Suitable for front wheel drive or all-wheel drive vehicles. For use in automatic gearboxes of Japanese, Korean and American car manufacturers.

SPECIFICATIONS

Suitable for use in various OEMs such as HYUNDAI, KIA, and other 6 speed automatic transmissions requiring a SP-IV automatic transmission fluid.

FEATURES & BENEFITS

- Superior wear protection and reliable friction properties for a consistent operation of transmission systems, contributing to prolonged transmission life.
- Reduced friction to improve automatic gearboxes reaction during engine start up.
- Excellent oxidation properties to prevent fluid breakdown at high operating temperatures, making fluid stable under severe driving conditions.







TYPICAL PROPERTIES

QATOL ULTRA TRANS ATF SP-IV	TYPICAL VALUES
Color	Red
Density @ 35°C , kg/m3	0.83
Kinematic Viscosity mm2 /s @100 0C	5.5
Kinematic Viscosity mm2 /s @40 0C	26.76
Viscosity Index	155

HAZARDS

This oil used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

PACKING

Available Packages: 1000L,208L,60L,20L, 5L, 4L,1L

