

QATOL SUPER COOL AFSC-33%CONC (OAT-TYPE)

QATOL SUPER COOL AFSC-33%CONC (OAT-TYPE) is ready to use coolant which is premixed with water. Specially designed formula is based on Mono Ethylene Glycol (MEG) and suitable corrosion inhibitors to provide supreme protection against frost and corrosion.

QATOL SUPER COOL AFSC-33%CONC (OAT-TYPE) is fortified with anti-rust and anti-corrosion additives. It has a very low freezing point and provides efficient heat transfer at high engine operating temperatures.

It is premixed with demineralized water for using as ready to use cooling and heat transfer fluid in internal combustion engines.

QATOL SUPER COOL AFSC-33%CONC (OAT-TYPE) is recommended for use in cooling systems of all types of liquid cooled automotive and industrial engines where such types of coolants are used. (Please refer OEM manual for recommended coolant).

SPECIFICATIONS

QATOL SUPER COOL AFSC-33%CONC (OAT-TYPE) meets following specifications

- Deutz DQC CB14, DQC CC14

KEY BENEFITS

- It is formulated to provide effective corrosion protection to cooling system and engine parts made out of ferrous and non-ferrous metals.
- Excellent protection of all hard metals in the cooling system and engine
- It provides round the year protection against frost and boiling.
- It is compatible with seals.

KEY PROPERTIES

| PROPERTIES | TEST METHOD | TYPICAL VALUES | UNIT |
|-----------------------------|-------------|----------------|-------------------|
| MEG Concentration | - | 33% | - |
| Specific Gravity @ 15 °C | ASTM D-1122 | 1060 – 1072 | kg/m ³ |
| Freezing Point (Max.) | ASTM D-3321 | -27 | °C |
| Reflux Boiling Point (Min.) | ASTM D-1120 | 105 | °C |
| pH value | ASTM D-1287 | 7-11 | - |
| Reserve Alkalinity (Min.) | ASTM D-1121 | 8-9 | - |

HAZARDS

This oil used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

PACKING

Available Packages: 1000L,200L,60L,20L, 5L, 4L,1L