

QATOL EXTRA PLUS GASOLINE ENGINE OIL 10W40 API SN

High performance , Synthetic Based Gasoline Engine Oil

QATOL EXTRA PLUS GASOLINE ENGINE OIL SAE 10W40 has been developed to meet the most stringent requirements of gasoline engines of wide range of carmakers.

QATOL EXTRA PLUS GASOLINE ENGINE OIL SAE 10W40 is an all-season synthetic oil that can be used under the most difficult operating conditions (highways, congested city traffic, etc).

APPLICATIONS

- For all types of modern gasoline-powered engines found in passenger cars, SUVs, light vans and light trucks.
- It is also suitable to turbocharged, multi-valve and direct injection engines.
- It is perfectly adapted to all vehicles equipped with catalysts.
- All types of gasoline Sports cars with large displacements and high outputs, high-performance passenger cars, racing- specification cars.
- Suitable & exceeds the performance level of most European, Japanese and American car manufactures requiring API SN oils.

SPECIFICATIONS

QATOL EXTRA PLUS GASOLINE ENGINE OIL SAE 10W40 meets and exceeds requirements of international standards and manufacturer requirements

API SN,

ACEA A3/B4,

MB 229.5,

BMW LL-01,

Renault RN0700/RN0710,

FEATURES & BENEFITS

- Formulated for reliable protection against harmful sludge and varnish formation and helps improve engine performance.
- Improved Fuel Economy & Reduction in Emission.
- Outstanding oxidation Stability at high temperatures.
- Excellent Engine cleanliness and water resistance.
- Ensuring sustainable high performance and extended oil drain intervals.
- Excellent shear stability, maintains viscosity grade.

TYPICAL PROPERTIES

QATOL EXTRA PLUS GASOLINE ENGINE OIL SAE 10W40 API SN	Typical value
Density @ 35°Ckg/m ³	0.85
Kinematic Viscosity: mm ² /s @ 40 °C	104.7
mm ² /s @100 °C	15.2
Viscosity Index	153
TBN mg KOH/g	>6
Flash Point COC, °C	>210
Pour Point, °C	-36

HAZARDS

This oil used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

PACKING

Available Packages: 1000L,208L,60L,20L, 5L, 4L,1L