

QATOL Q-TEC BRAKE FLUID DOT 4

Fully Synthetic

QATOL Q-TEC BRAKE FLUID DOT 4 is a synthetic fluid with a high boiling point studied for disc and drum brakes,

A critical aspect of the brake fluids is their hygroscopicity. During the exercise, they tend to absorb moisture with consequent decrease in the boiling point. Therefore, prolonged braking action that heats the fluid can cause a vapour lock (formation of vapour bubbles). QATOL Q-TEC BRAKE FLUID DOT 4 prevents this from happening. It can be mixed with other brake fluids that meet the same specifications

APPLICATIONS

QATOL Q-TEC BRAKE FLUID DOT 4 Brake Fluid meets the recognised standards for clutch and brake fluids as demanded by leading motor vehicle manufacturers, all hydraulically operated motor vehicle braking systems (drum and disc types) for which a DOT 4, SAE J1704 or ISO 4925 Class 4 fluid is specified, vehicles with anti-lock (ABS) braking systems, hydraulic clutch systems requiring conventional fluids, Passenger cars, commercial road transport, off-highway vehicles, agricultural tractors and motorcycles Brake Fluid DOT 4 is compatible with other brands of DOT 4/DOT 3 brake fluid

SPECIFICATIONS

FMVSS 116, DOT 4
SAE J 1703 / J 1704,
ISO 4925 class 3, class 4

FEATURES & BENEFITS

- High boiling point (above 260°C)
- Low viscosity at -40 ° C,
- Minimum swelling on rubber surfaces,
- Anti-corrosive properties on all metals,
- High lubricant power,
- Good chemical stability.

TYPICAL PROPERTIES

QATOL Q-TEC BREAK FLUID DOT 4	TYPICAL VALUES
Appearance	Clear & Bright
Density @ 20°C , kg/m ³	1.05
Kinematic Viscosity mm ² /s @100 0C	2.0
Kinematic Viscosity mm ² /s @40 0C	14
ERBP, °C	260
Wet ERBP, °C	165

HAZARDS

This oil used as recommended and for the application for which it has been designed does not present any particular health & environmental risk.

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to Material Safety Data Sheet.

PACKING

Available Packages: 250 ml, 500 ml